

ORGANIC ETCH TWITCH

Acoustics » Acoustic Panels



Brand: **Zintra**

1300 306 399

info@baresque.com.au

baresque.com.au

1 of 5

ORGANIC ETCH TWITCH

Acoustics » Acoustic Panels



ASH



BARK



BRICK



CADET



CHAMBRAY



COBALT



ECRU



FOSSIL



FROST



GRASS




GREIGE



IVORY




LINEN




MALACHITE



MANDARIN



MIDNIGHT



OCHRE



OLIVE



PEBBLE



PEWTER



SKY



SMOKE



SUNSHINE



TAR

ORGANIC ETCH TWITCH

Acoustics » Acoustic Panels



Organic Etch Twitch undulating, simple, tactile, and imperfectly perfect.

- Solution Dyed Yarns
- Easy Install
- Extended Warranty
- Easy Clean
- Absorbs Noise
- Acoustic

Description

Combining undulating bursts of lines, thoughtfully overlaid to a traditional herringbone base. Organic Etch Twitch makes creative use of columns and short parallel lines, where lines in one column slope in one way and lines in adjacent columns slope the opposite. The design is further enhanced with the addition of vertical lines, deepening the textural element of the design.

Available in the full 24-color range, choose from complementary natural tones like Linen, Pebble, and Slate, or be brave and make the designs pop with the vibrancy of Sunshine, Ochre or Cobalt.

Lightweight and easy to cut Organic Etch is the perfect acoustic alternative to traditional commercial wallcoverings.

Dimensions

Available in 1/2" (12mm) ONLY

Standard Sheet Size

48" (1219mm) w x 108" (2743mm) h x 1/2" (12mm) d

ORGANIC ETCH TWITCH

Acoustics » Acoustic Panels

PET Colours	24 Colors – Ash, Bark, Brick, Cadet, Chambray, Cobalt, Ecru, Fossil, Frost, Grass, Greige, Ivory, Linen, Malachite, Mandarin, Midnight, Ochre, Olive, Pebble, Sky, Smoke, Sunshine, Tar.
Material	Zintra Acoustic Panel - 100% Solution Dyed (Color Through) Polyester
Fire Rating	<p>Tested in accordance with AS ISO 9705 2003 for the purpose of determining the Group Number classification required by the Building Code of Australia for the control of fire spread on interior wall and ceiling linings.</p> <p>Classification - Group 1 Specific Extinction - Less than 250m²/kg</p>
Warranty	5-year warranty. Visit baresque.com.au/warranty for complete details.
Assembly & Delivery	<p>Ships Flat Pack</p> <p>Refer installation Instructions</p>
Suggested Installation	<p>Be sure to support the panel during installation to avoid bowing or creasing.</p> <p>Adhere to substrate using contact adhesive, Liquid Nails or Z clips.</p> <p>Panel can also be mechanically fixed using details similar to glass fittings.</p> <p>Download the Handling and Installation guide for full instructions.</p>
How to Specify	<ol style="list-style-type: none">1. Select PET Color2. Select Organic Etch Pattern
Care Instructions	<p>Vacuum to remove dust.</p> <p>Dab Zintra with a damp clean cloth and mild solution of liquid detergent and warm water. Repeat using only clean water, then pat dry with a lint free cloth.</p> <p>For difficult stains, use a solution of household bleach (10% bleach / 90% water). To remove the bleach, repeat using a clean, water dampened cloth, then pat dry.</p> <p>Always test in an inconspicuous area first and if you don't see the expected results, contact us.</p>

ORGANIC ETCH TWITCH

Acoustics » Acoustic Panels

Additional Comments NRC 0.45 - 0.75

COLOUR DISCLAIMER:

Due to inconsistencies with monitors, and the calibration of your screen, colours may display differently. As they may not be an accurate representation of the true colour we advise requesting a sample.
