Acoustics » Acoustic Panels



Brand: Baresque



Acoustics » Acoustic Panels

ASH	BARK	BRICK	CADET	CHAMBRAY
COBALT	ECRU	FOSSIL	FROST	GRASS
GREIGE	IVORY	LINEN	MALACHITE	MANDARIN
MIDNIGHT	OCHRE	OLIVE	PEBBLE	PEWTER
SKY	SMOKE	SUNSHINE	TAR	

1300 306 399 info@baresque.com.au baresque.com.au



Acoustics » Acoustic Panels



Simple, tactile, and imperfectly perfect Organic Etch Stripe partners perfectly with Organic Etch Herringbone Stripe.

 Solution Dyed Yarns Easy Install Bleach Cleanable 	 Extended Warranty Easy Clean Acoustic 	 Absorbs Noise Environmentally Friendly 		
DescriptionOrganic Etch Stripe is a quieter, more simplified pattern that can be ordination of design with Organic Etch Herringbone Stripe to bring a and dimension to your space.Available in the full 24-color range, choose from complementary nat Linen, Pebble, and Slate, or be brave and make the designs pop with of Sunshine, Ochre or Cobalt.				
	Lightweight and easy to cut Organic E traditional commercial wallcoverings.	tch is the perfect acoustic alternative to		
Dimensions	Available in 1/2" (12mm) ONLY			
	Standard Sheet Size			
	48" (1219mm) w x 108" (2743mm) h x 1/2" (12mm)			



Acoustics » Acoustic Panels

PET Colours	24 Colors – Ash, Bark, Brick, Cadet, Chambray, Cobalt, Ecru, Fossil, Frost, Grass, Greige, Ivory, Linen, Malachite, Mandarin, Midnight, Ochre, Olive, Pebble, Sky, Smoke, Sunshine, Tar.	
Composition	Zintra Acoustic Panel - 100% Solution Dyed (Color Through) Polyester	
Environmental Info	Easily recycled through standard recycling channels	
Fire Rating	Tested in accordance with AS ISO 9705 2003 for the purpose of determining the Group Number classification required by the Building Code of Australia for the control of fire spread on interior wall and ceiling linings.	
	Classification - Group 1 Specific Extinction - Less than 250m²/kg	
Warranty	5-year warranty. Visit baresque.com.au/warranty for complete details.	
Lead Time	• 2-3 weeks.	
	• Additonal 1-week for Western Australia.	
Assembly & Delivery	Ships Flat Pack	
	Refer installation Instructions	
How to Specify	1. Select PET Color	
	2. Select Organic Etch Pattern	
Care Instructions	Vacuum to remove dust.	
	Dab Zintra with a damp clean cloth and mild solution of liquid detergent and warm water. Repeat using only clean water, then pat dry with a lint free cloth.	
	For difficult stains, use a solution of household bleach (10% bleach / 90% water). To remove the bleach, repeat using a clean, water dampened cloth, then pat dry.	
	Always test in an inconspicuous area first and if you don't see the expected results, contact us.	
Customisable	The Zintra Acoustic Solutions range is customisable to your project. Please get in touch with your local contact for details.	



Additional Comments NRC 0.45 - 0.75

COLOUR DISCLAIMER:

Due to inconsistencies with monitors, and the calibration of your screen, colours may display differently. As they may not be an accurate representation of the true colour we advise requesting a sample.

