

Brand: **Reatec**

Applications: Walls, Joinery



Color is a 122cm wide architectural film. Resistant to stain, anti-mould, colorfast, washable and scrubbable.

✓ Bleach Cleanable

Description	Reatec is a durable and realistic architectural film with a pressure sensitive adhesive and air removal system backing. Utilising state of the art, multi layer printing and minute embossing, its appearance is almost indistinguishable from real wood or stone. Reatec is stain and solvent/chemical resistant, anti-bacterial, anti-mould, colorfast, washable, scrubbable, and abrasion resistant. A pdf with full Reatec Test Results can be found on the product Downloads tab on the website. Reatec can be stretched to cover the corners and curves and is suitable for both indoor and outdoor uses including kitchens and bathrooms. Go to the DOWNLOADS tab for our Reatec Additional Spec Sheet and Installation Guide.
Composition	Reatec is a durable and realistic architectural film with a pressure sensitive adhesive and air removal system backing 350 g/m²
Pattern Repeat Size	N/A
Fire Rating	Tested in accordance with AS ISO 9705 2003 for the purpose of determining the Group Number classification required by the Building Code of Australia for the control of fire spread on interior wall and ceiling linings. Classification - Group 1 Specific Extinction - Less than 250m²/kg
Lead Time	 2-weeks (approx.) from Wednesday, subject to stock availability. Additional 1-week for Western Australia. Express delivery is available subject to a surcharge. Contact Baresque for details and pricing.
Suggested Installation	Reatec is a specialised product and should only be installed by a trained installer. It is strongly recommended that the installation instructions from our product downloads are read and understood. As Reatec is a thin film, the substrate should be prepared as smooth as possible to avoid visible unevenness. Reatec can be installed and repaired on-site, resulting in almost no downtime for both interior and exterior applications. Feel free to contact Baresque with any installation questions.



Care Instructions	Wipe material with a clean, soft cloth dampened with a mild solution of liquid detergent and warm water. Repeat using only clean water, then dry with a lint free cloth.		
	Avoid using wax polishes, solvents or concentrated abrasives.		
	For more difficult stains, dampen a soft white cloth with a solution of household bleach (10% bleach / 90% water). Rub gently. Rinse with a water dampened cloth to remove bleach concentration.		
	Always test in an inconspicuous area first. If care instructions don't deliver the expected results, cease cleaning method immediately and contact Baresque for assistance.		
Warranty	2-year warranty. Visit baresque.com.au/warranty for complete details.		



Wallcoverings » Architectural Film

Colour & Finish Options





TA4733	TA4734	TA4735	TA4736	TA4737
TA4738	TA4739	TA4740	TA4741	TA4742
TA4743	TA4744	TA4745	TA4746	TA4747
TA4748	TA4749	TA4750	TA4751	TA4752
TA4754	TA4755	TA4756	TA4757	TA4758



TA4759	TA4760	TA4763	TA4764	TA4765
TA4766	TA4767	TA4768	TA4769	TA4770
TA4772	TA4773	TA4774	TA4775	TA4776
TA4777	TA4778	TA4779	TA4781	TA4782
TA4783	TA4784	TA4786	TA4787	TA4789



TA4791	TA4793	TA4794	TA4795	TA4796
TA4798	TA4800	TA4801	TX4597	TX4802
TX4803	TX5341	TX5342	TX5343	TX5344
TX5345	TX5346	TX5347	TX5348	TX5349
TX5350	TX5351	TX5352	TX5353	TX5355



Wallcoverings » Architectural Film



TX5356

