

STONE

Wallcoverings » Architectural Film



Brand: **Reatec**

STONE

Wallcoverings » Architectural Film




TC4577



TC4578



TC4579




TC4580




TC4581



TC4584



TC4586



TC4587



TC5207



TC5208



TC5211



TC5212



TC5213



TC5214



TC5553




TC5554



TN5209



TN5210



TN5319



TN5320



TN5321



TN5322



TN5323



TN5324



TN5325

STONE

Wallcoverings » Architectural Film

Reatec Stone reflects traditional Natural marble Stone, offering a new and innovative way to design with Stone that's lightweight with high durability

✓ Bleach Cleanable

Description	<p>Reatec is a durable and realistic architectural film with a pressure sensitive adhesive and air removal system backing.</p> <p>Utilising state of the art, multi layer printing and minute embossing, its appearance is almost indistinguishable from real wood or stone. Reatec is stain and solvent/chemical resistant, anti-bacterial, anti-mould, colorfast, washable, scrubbable, and abrasion resistant.</p> <p>A pdf with full Reatec Test Results can be found on the product Downloads tab on the website.</p> <p>Reatec can be stretched to cover the corners and curves and is suitable for both indoor and outdoor uses including kitchens and bathrooms. Go to the DOWNLOADS tab for our Reatec Additional Spec Sheet and Installation Guide.</p>
Product Code	WC.STONE.RTC
Roll Size	122cm wide x 50m - Available by the lineal metre
Composition	Reatec is a durable and realistic architectural film with a pressure sensitive adhesive and air removal system backing 350 g/m ²
Pattern Repeat Size	N/A
Fire Rating	<p>Tested in accordance with AS ISO 9705 2003 for the purpose of determining the Group Number classification required by the Building Code of Australia for the control of fire spread on interior wall and ceiling linings.</p> <p>Classification - Group 1 Specific Extinction - Less than 250m²/kg</p>
Warranty	2-year warranty. Visit baresque.com.au/warranty for complete details.
Lead Time	<ul style="list-style-type: none">• 2-weeks (approx.) from Wednesday, subject to stock availability.• Additional 1-week for Western Australia.• Express delivery is available subject to a surcharge. Contact Baresque for details and pricing.

STONE

Wallcoverings » Architectural Film

Suggested Installation

Reatec is a specialised product and should only be installed by a trained installer.

It is strongly recommended that the installation instructions from our product downloads are read and understood.

As Reatec is a thin film, the substrate should be prepared as smooth as possible to avoid visible unevenness.

Reatec can be installed and repaired on-site, resulting in almost no downtime for both interior and exterior applications.

Feel free to contact Baresque with any installation questions.

Care Instructions

Wipe material with a clean, soft cloth dampened with a mild solution of liquid detergent and warm water. Repeat using only clean water, then dry with a lint free cloth.

Avoid using wax polishes, solvents or concentrated abrasives.

For more difficult stains, dampen a soft white cloth with a solution of household bleach (10% bleach / 90% water). Rub gently. Rinse with a water dampened cloth to remove bleach concentration.

Always test in an inconspicuous area first. If care instructions don't deliver the expected results, cease cleaning method immediately and contact Baresque for assistance.

STONE

Wallcoverings » Architectural Film

Colour & Finish Options