

LIGHTBLOCKS ICE


Acrylics, Resin & Laminates » Acrylics/Resin



Brand: **Lightblocks**

LIGHTBLOCKS ICE

Acrylics, Resin & Laminates » Acrylics/Resin



ICE

LIGHTBLOCKS ICE

Acrylics, Resin & Laminates » Acrylics/Resin

Ice is a fully refinishable, soft to the touch, multi-dimensional resin panel.

✓ **Bleach Cleanable**

✓ **Fully Refinishable**

✓ **Finger print proof**

✓ **Soft touch**

✓ **Thermoformable**

✓ **Seamless Joins**

Description

Ice is a fully refinishable, soft to the touch, multi-dimensional resin panel

FEATURES

- * Bleach cleanable
- * Full refinishable
- * Finger print proof
- * Soft touch
- * Thermoformable
- * Seamless joins

Dimensions

Sheet Size:

2440mm x 1220mm - 3mm, 6mm, 10mm, 15mm, 20mm, 30mm

3000mm x 1000mm - 3mm, 6mm, 10mm

Composition

Lightblocks resin

Finishes

Surface Finish : Matt

Environmental Info

Easily recycled. Contact your nearest Baresque branch for details.

Fabrication Techniques

Standard wood working tools. See Baresque Lightblocks Fabrication Guide for more details.

How to Specify

1. Product/Colour = Ice
2. Sheet size
3. Thickness

LIGHTBLOCKS ICE

Acrylics, Resin & Laminates » Acrylics/Resin

Care Instructions

Always use a clean, white, soft cloth. When cleaning, never scrub Lightblocks. Gently wipe the surface.

Use cloth with any of the following in preferred order of use:

* Clear warm water

* Mild solution of liquid detergent and warm water

* Kerosene, hexane, or aliphatic naphtha, or any acrylic cleaner, such as Novus. Always follow manufacturer's recommended use and safety procedures.

Remove any oily residue left behind from solvent cleaning with detergent and water.

For more difficult stains, dampen a soft white cloth with a solution of household bleach (10% bleach / 90% water). Rub gently. Rinse with a water dampened cloth to remove bleach concentration.

DO NOT USE glass cleaning products, acetone, gasoline, benzene, lacquer thinner, chlorinated solvents, gritty abrasive scouring compounds, or alkaline cleaners as damage to the sheet will occur.

DO NOT USE a squeegee, scraper, or synthetic rags that may scratch.

if there is only a light scratch, refinishing can be achieved by rubbing the area in a random circular motion with a fine steel scouring pad (Scotch-brite).

Test in an inconspicuous area before attempting a main area on the job.

LIGHTBLOCKS ICE

Acrylics, Resin & Laminates » Acrylics/Resin

Colour & Finish Options