

# POST

Wallcoverings » Commercial Wallcoverings



Brand: **York**

Collection: **Restoration  
Elements**

# POST

Wallcoverings » Commercial Wallcoverings



COLOURWAY CARD




MRE1640  
WARMSTONE



MRE1641 OPTIC  
WHITE




MRE1642 NATURAL  
WHITE




MRE1643 ALUMINUM



MRE1644 PEARL  
TRAX




MRE1645 ASH



MRE1646 SUN DECK




MRE1647 GRAPHITE



MRE1648 SLATE



MRE1649 SHADOW



MRE1650 ROTARY

# POST

Wallcoverings » Commercial Wallcoverings

Post is a 132cm wide commercial wallcovering with a texturized vertical pattern that's available in 11 colourways.

✓ **Low VOC**

✓ **Bleach Cleanable**

✓ **Moisture Repellant**

✓ **Moisture Barrier**

✓ **Anti-Microbial**

Pattern Repeat Size Random

## Sustainability

- Low Voc
- Water-Based inks
- Member of the US Green Building Council
- York commercial grade vinyl contains attributes to contribute towards LEED building certification
- Certified to NSF/ANSI 342 Sustainability Assessment for Wallcovering Products

## Fire Rating

Tested in accordance with AS ISO 9705 2003 for the purpose of determining the Group Number classification as required by the Building Code of Australia for the control of fire spread on interior wall and ceiling linings.

The result achieved was:  
Classification - Group 2  
Specific Extinction - Less than 250m<sup>2</sup>/kg

## Warranty

5-year warranty. Visit [baresque.com.au/warranty](https://www.baresque.com.au/warranty) for complete details.

## Lead Time

- 2-weeks (approx.) from Wednesday, subject to stock availability.
- Additional 1-week for Western Australia.
- Express delivery is available subject to a surcharge. Contact Baresque for details and pricing.

## Suggested Installation

Reverse hang / overlap and double cut.

Baresque recommends and supply Roman brand adhesives and primers.

# POST

Wallcoverings » Commercial Wallcoverings

---

## Care Instructions

Use cloth with any of the following in preferred order of use:

1: Clear warm water

2: Mild solution of liquid detergent and warm water

3: Isopropyl Alcohol (a.k.a. rubbing alcohol)

Remove any detergent with a clean, damp cloth. Gently pat dry.

For more difficult stains, dampen a soft white cloth with a solution of household bleach (10% bleach / 90% water). Rub gently.

Rinse with a water dampened cloth to remove bleach concentration.

Do not use solvent based or concentrated abrasive cleaning agents, lacquer thinners or nail polish remover as these may cause discolouration over a period of time.

Always test in an inconspicuous area first.

If care instructions don't deliver the expected results, cease cleaning method immediately and contact Baresque for assistance.

---

# POST

Wallcoverings » Commercial Wallcoverings

---

## Colour & Finish Options