

Wallcoverings » Commercial Wallcoverings



Brand: Xorel

Applications: Walls, Upholstery



DOVER Wallcoverings » Commercial Wallcoverings







Random striations gives Dover a pattern a silk look, with a very subtle herringbone weave structure. Available in 4 colourways.

 Environmentally Friendly Anti-Bacterial Extreme Durability 	 PVC-Free Ultra Performance Extended Warranty 	 Phthalate Free Bleach Cleanable Acoustic
Description	ion Xorel is a technologically advanced and environmentally sound problem solvin woven textile which enables a wide range of design possibilities to be realized the high performance characteristics of Xorel emanate from the yarn. Simply p nothing is added to the woven product to enhance performance; no finishes, n coatings.	
	A unique design approach that marries technology, craft,and textile experimentation, Xoreal delivers beautiful performance for workplace,hospitals, hotels, schools and beyond. Made from the rapidly renewable sugarcane plant, Biobased Xorel generates a significantly reduced carbon footprint over fossil-duel based products.	
Composition	100% Xorel.	
	Available Unbacked (for wrapped panels)	or
	X-Protect Wall (for wallcoverings),	
	X-Protect Sit (for upholstery) Acrylic (for	wrapped panels with glue) backings
Environmental Info	Xorel's high performance does not come a high standards for sustainability.	t an environmental cost as it achieves
	All testing/certifying is done by third parts Scientific Certification Systems (SCS) – In Biobased Content (LEVELS 3/4)- USDA Bi Regulations (PREFERRED)- Cradle to Crad (GOLD)- NSF – FACTS certification (NSF 3	door Air Quality (GOLD)- Vincotte – obased – Meeting Government Biobased dle Institute – Full Lifecycle Assessment
	Xorel products can also help a project ach commercial interiors:Material Sourcing (Ra Quality (SCS Indoor Advantage Gold)Mate Gold)Material Transparency (Healthy Proc	apidly Renewable Content)Indoor Air erial Optimization (Cradle to Cradle
Pattern Repeat Size	101cm Lenght X Full Width. No match requ	uired



DOVER

Wallcoverings » Commercial Wallcoverings

Notified Schools and Present X-Protect Wall - 132cm X-Protect Sit - 137cm Acrylic Backed - 137cm x Approx 60m - available by the lineal metre. MINIMUM ORDER for X-Protect Sit - 5 lineal metres Abrasion 1.000.000 double rubs Fire Rating As a wallcovering - Tested in accordance with AS/NZS 3837 and AS 5637.1:2015 for the purposes of Group Number Classification as specified in the NCC Volume One Specification - C110 Clause 4 Classification - Group 1 Specific Extinction - Less than 250 m²/kg As a fabric - Tested in accordance with AS1530.3 Spread of Flame Index - 0 Smoke Developed Index - 5 Smoke Developed Index - 5 Lead Time • 5-weeks (approx) from Wednesday subject to stock availability. • Additional 1-week for Western Australia. • Unbacked 2-3 weeks. • Express delivery is available subject to a surcharge. Contact Baresque for details and pricing Suggested As a wallcovering - trim selvedge and butt join. Download the Installation Instructions for details. Baresque recommends and supply Roman brand adhesives and primers.	Roll Size	Unbacked - 142cm
X-Protect Sit - 137cm Acrylic Backed - 137cm x Approx 60m - available by the lineal metre. MINIMUM ORDER for X-Protect Sit - 5 lineal metres MINIMUM ORDER for Acrylic Backed - 15 lineal metres Abrasion 1.000.000 double rubs Fire Rating As a wallcovering - Tested in accordance with AS/NZS 3837 and AS 5637.1:2015 for the purposes of Group Number Classification as specified in the NCC Volume One Specification C110 Clause 4 Classification - Group 1 Specific Extinction - Less than 250 m²/kg As a fabric - Tested in accordance with AS1530.3 Spread of Flame Index - 0 Smoke Developed Index - 5 Smoke Developed Index - 5 Lead Time • 5-weeks (approx) from Wednesday subject to stock availability. • Additional 1-week for Western Australia. • Unbacked 2-3 weeks. • Express delivery is available subject to a surcharge. Contact Baresque for details and pricing Suggested Installation As a wallcovering - trim selvedge and butt join. Download the Installation Instructions for details.		
Acrylic Backed - 137cm x Approx 60m - available by the lineal metre. MINIMUM ORDER for X-Protect Sit - 5 lineal metres MINIMUM ORDER for Acrylic Backed - 15 lineal metres Abrasion 1.000.000 double rubs Fire Rating As a wallcovering - Tested in accordance with AS/NZS 3837 and AS 5637.1:2015 for the purposes of Group Number Classification as specified in the NCC Volume One Specification C1.10 Clause 4 Classification - Group 1 Specific Extinction - Less than 250 m²/kg As a fabric - Tested in accordance with AS1530.3 Spread of Flame Index - 0 Smoke Developed Index - 5 Smoke Developed Index - 5 Lead Time • 5-weeks (approx) from Wednesday subject to stock availability. • Additional 1-week for Western Australia. • Unbacked 2-3 weeks. • Express delivery is available subject to a surcharge. Contact Baresque for details and pricing Suggested Installation As a wallcovering - trim selvedge and butt join.		
MINIMUM ORDER for X-Protect Sit - 5 lineal metres MINIMUM ORDER for Acrylic Backed - 15 lineal metres Abrasion 1.000.000 double rubs Fire Rating As a wallcovering - Tested in accordance with AS/NZS 3837 and AS 5637.1:2015 for the purposes of Group Number Classification as specified in the NCC Volume One Specification C110 Clause 4 Classification - Group 1 Specific Extinction - Less than 250 m³/kg As a fabric - Tested in accordance with AS1530.3 Spread of Flame Index - 0 Smoke Developed Index - 5 Smoke Developed Index - 5 Lead Time -5-weeks (approx) from Wednesday subject to stock availability. • Additional 1-week for Western Australia. • Unbacked 2-3 weeks. • Express delivery is available subject to a surcharge. Contact Baresque for details and pricing Suggested Installation As a wallcovering - trim selvedge and butt join. Download the Installation Instructions for details.		
MINIMUM ORDER for Acrylic Backed - 15 lineal metres Abrasion 1.000.000 double rubs Fire Rating As a wallcovering - Tested in accordance with AS/NZS 3837 and AS 5637.1:2015 for the purposes of Group Number Classification as specified in the NCC Volume One Specification C1.10 Clause 4 Classification - Group 1 Specific Extinction - Less than 250 m²/kg As a fabric - Tested in accordance with AS1530.3 Spread of Flame Index - 0 Smoke Developed Index - 5 Smoke Developed Index - 5 Lead Time • 5-weeks (approx) from Wednesday subject to stock availability. • Additional 1-week for Western Australia. • Unbacked 2-3 weeks. • Express delivery is available subject to a surcharge. Contact Baresque for details and pricing Suggested Installation As a wallcovering - trim selvedge and butt join. Download the Installation Instructions for details.		
Abrasion 1.000.000 double rubs Fire Rating As a wallcovering - Tested in accordance with AS/NZS 3837 and AS 56371:2015 for the purposes of Group Number Classification as specified in the NCC Volume One Specification C1.10 Clause 4 Classification - Group 1 Specific Extinction - Less than 250 m²/kg As a fabric - Tested in accordance with AS1530.3 Spread of Flame Index - 0 Smoke Developed Index - 5 Smoke Developed Index - 5 Lead Time • 5-weeks (approx) from Wednesday subject to stock availability. • Additional 1-week for Western Australia. • Unbacked 2-3 weeks. • Express delivery is available subject to a surcharge. Contact Baresque for details and pricing Suggested As a wallcovering - trim selvedge and butt join. Download the Installation Instructions for details.		MINIMUM ORDER for X-Protect Sit - 5 lineal metres
Fire Rating As a wallcovering - Tested in accordance with AS/NZS 3837 and AS 5637.1:2015 for the purposes of Group Number Classification as specified in the NCC Volume One Specification C1.10 Clause 4 Classification - Group 1 Specific Extinction - Less than 250 m²/kg As a fabric - Tested in accordance with AS1530.3 Spread of Flame Index - 0 Smoke Developed Index - 5 Smoke Developed Index - 5 Lead Time • 5-weeks (approx) from Wednesday subject to stock availability. • Additional 1-week for Western Australia. • Unbacked 2-3 weeks. • Express delivery is available subject to a surcharge. Contact Baresque for details and pricing Suggested As a wallcovering - trim selvedge and butt join. Download the Installation Instructions for details.		MINIMUM ORDER for Acrylic Backed - 15 lineal metres
the purposes of Group Number Classification as specified in the NCC Volume One Specification C1.10 Clause 4 Classification - Group 1 Specific Extinction - Less than 250 m²/kg As a fabric - Tested in accordance with AS1530.3 Spread of Flame Index - 0 Smoke Developed Index - 5 Lead Time • 5-weeks (approx) from Wednesday subject to stock availability. • Additional 1-week for Western Australia. • Unbacked 2-3 weeks. • Express delivery is available subject to a surcharge. Contact Baresque for details and pricing Suggested As a wallcovering - trim selvedge and butt join. Download the Installation Instructions for details.	Abrasion	1.000.000 double rubs
Specific Extinction - Less than 250 m²/kg As a fabric - Tested in accordance with AS1530.3 Spread of Flame Index - 0 Smoke Developed Index - 5 Lead Time • 5-weeks (approx) from Wednesday subject to stock availability. • Additional 1-week for Western Australia. • Unbacked 2-3 weeks. • Express delivery is available subject to a surcharge. Contact Baresque for details and pricing Suggested Installation As a wallcovering - trim selvedge and butt join. Download the Installation Instructions for details.	Fire Rating	the purposes of Group Number Classification as specified in the NCC Volume One
As a fabric - Tested in accordance with AS1530.3 Spread of Flame Index - 0 Smoke Developed Index - 5 Lead Time • 5-weeks (approx) from Wednesday subject to stock availability. • Additional 1-week for Western Australia. • Unbacked 2-3 weeks. • Express delivery is available subject to a surcharge. Contact Baresque for details and pricing Suggested Installation As a wallcovering - trim selvedge and butt join. Download the Installation Instructions for details.		Classification - Group 1
Spread of Flame Index - 0 Smoke Developed Index - 5 Lead Time • 5-weeks (approx) from Wednesday subject to stock availability. • Additional 1-week for Western Australia. • Unbacked 2-3 weeks. • Express delivery is available subject to a surcharge. Contact Baresque for details and pricing Suggested As a wallcovering - trim selvedge and butt join. Download the Installation Instructions for details.		Specific Extinction - Less than 250 m²/kg
Smoke Developed Index - 5 Lead Time • 5-weeks (approx) from Wednesday subject to stock availability. • Additional 1-week for Western Australia. • Unbacked 2-3 weeks. • Express delivery is available subject to a surcharge. Contact Baresque for details and pricing Suggested As a wallcovering - trim selvedge and butt join. Download the Installation Instructions for details.		As a fabric - Tested in accordance with AS1530.3
Lead Time • 5-weeks (approx) from Wednesday subject to stock availability. • Additional 1-week for Western Australia. • Unbacked 2-3 weeks. • Express delivery is available subject to a surcharge. Contact Baresque for details and pricing Suggested Installation As a wallcovering - trim selvedge and butt join. Download the Installation Instructions for details.		Spread of Flame Index - 0
 Additional 1-week for Western Australia. Unbacked 2-3 weeks. Express delivery is available subject to a surcharge. Contact Baresque for details and pricing Suggested As a wallcovering - trim selvedge and butt join. Download the Installation Instructions for details. 		Smoke Developed Index - 5
 Unbacked 2-3 weeks. Express delivery is available subject to a surcharge. Contact Baresque for details and pricing Suggested As a wallcovering - trim selvedge and butt join. Download the Installation Instructions for details. 	Lead Time	 5-weeks (approx) from Wednesday subject to stock availability.
 Express delivery is available subject to a surcharge. Contact Baresque for details and pricing Suggested As a wallcovering - trim selvedge and butt join. Download the Installation Instructions for details. 		 Additional 1-week for Western Australia.
and pricing Suggested Installation Download the Installation Instructions for details.		• Unbacked 2-3 weeks.
Installation Download the Installation Instructions for details.		
Download the Installation Instructions for details.		As a wallcovering - trim selvedge and butt join.
Baresque recommends and supply Roman brand adhesives and primers.		Download the Installation Instructions for details.
		Baresque recommends and supply Roman brand adhesives and primers.



Care Instructions	Xorel yarns are non-absorbent; dust and stains cannot penetrate them.
	Regular maintenance will keep the fabric looking new for many years. Periodic vacuuming will remove dust that may settle between the yarns.
	Most stains that dry between the yarns or on the surface can be eliminated by wiping the fabric with a cloth moistened with hot tap water. Some stains may require additional treatment. These stains can be cleaned with a variety of water or solvent based cleaners.
	When using solvent based cleaners on paperbacked Xorel fabric, test on a small area first. Residue from these cleaners must be removed with hot water and a clean sponge. After cleaning, towel dry.
	Hardened solids can be removed with stiff brush or a sharp-edged instrument without damaging the fabric. However, the brush or sharp instrument should not be used close to seams.
	Hospital grade disinfectant cleaners can be safely used on Xorel fabrics. Always follow the directions for the specific brand being used as contact times may vary depending on the product. Diluted bleach solution (up to 40%) can also be used on Xorel for disinfecting purposes.
	Always test in an inconspicuous area first. If care instructions don't deliver the expected results, cease cleaning method immediately and contact Baresque for assistance.
Warranty	7-year warranty. Visit baresque.com.au/warranty for complete details.
Additional Comments	Xorel is notable for its versatility in a wide range of projects; wherever both beauty and performance are required.
	"Wallcoverings Unbacked:
	Acoustically transparent, highly tackable, ability to self heal, yarns can ""move back: into position. Highly stable on panels and does not react to changes in humidity or moisture"
	Upholstery Backing: X-Protect Sit
	X-Protect Sit: A proprietary technology which prevents stains and moisture from passing through textile to the seat cushion.



Wallcoverings » Commercial Wallcoverings

Colour & Finish Options











COLOURWAY CARD

6123-10

6123-11

6123-12

-6123-13



Dove-6123-14

1300 306 399 info@baresque.com.au baresque.com.au

