

WOODWINDS

Wallcoverings » Commercial Wallcoverings



Brand: **Symphony**

Applications: **Walls**

1300 306 399

info@baresque.com.au

baresque.com.au

1 of 4

WOODWINDS

Wallcoverings » Commercial Wallcoverings

Woodwinds provides the wood feeling warmth with anti-microbial protection and low VOC for any environment.

- ✓ Bleach Cleanable
- ✓ 10% Recycled content
- ✓ HPD Certified
- ✓ Anti-Microbial
- ✓ Non-Phthalate
- ✓ Low VOC
- ✓ EPD Certified

Description

Wood wallcovering has long been a favourite of interior designers for its natural warmth and authentic beauty.

Designed to last, Woodwinds is the solution you're looking for to give your space a beautiful representation of earthly material that is cost-effective and versatile in any room.

Natural graining, knots, subtle colour shading, and texture make Woodwinds almost indistinguishable from genuine aged resources.

Composition Vinyl face on a woven backing 20oz (452 g/m²)

Environmental Info

Formaldehyde free

Heavy metals free

Perfluorooctanoic acid free

No solvent inks

Low VOC emissions. Any VOCs dissipate quickly (faster than paint) through normal ventilation and have no recognized adverse impact on indoor air quality.

Durability means products do not need to be replaced regularly due to wear and tear and being cleanable, vinyl products are ideal for helping keep commercial environments clean of bacteria.

Baresque will only deal with vinyl manufacturers that comply with applicable state and federal regulations, provide a factory that is safe and clean for its employees to work in, recycle scrap and inks during the manufacturing process to minimize waste related to production.

Pattern Repeat Size Not Applicable

Roll Size 137cm wide x 27.4m - Available by the lineal metre

Weight 452 (g/m²)

WOODWINDS

Wallcoverings » Commercial Wallcoverings

Fire Rating Tested in accordance with AS ISO 9705 2003 for the purpose of determining the Group Number classification as required by the Building Code of Australia for the control of fire spread on interior wall and ceiling linings.

The result achieved was:
Classification - Group 2
Specific Extinction - Less than 250m²/kg

Lead Time

- 2-weeks (approx.) from Wednesday, subject to stock availability.
- Additional 1-week for Western Australia.
- Express delivery is available subject to a surcharge. Contact Baresque for details and pricing.

Suggested Installation Non-reverse hang alternate drops/straight across match/overlap and double cut.
Baresque recommends and supplies Roman brand adhesives and primers.

Care Instructions Always use a clean, white, soft cloth.

Use cloth with any of the following in preferred order of use:

- 1: Clear warm water
- 2: Mild solution of liquid detergent and warm water
- 3: Isopropyl Alcohol (a.k.a. rubbing alcohol)

Remove any detergent with a clean, damp cloth. Gently pat dry.

For more difficult stains, dampen a soft white cloth with a solution of household bleach (10% bleach / 90% water). Rub gently.

Rinse with a water dampened cloth to remove bleach concentration.

DO NOT USE solvent based or concentrated abrasive cleaning agents, lacquer thinners, nail polish remover as these may cause discolouration over a period of time.

Always test in an inconspicuous area first. If care instructions don't deliver the expected results, cease cleaning method immediately and contact Baresque for assistance.

Warranty 5-year warranty. Visit [baresque.com.au/warranty](https://www.baresque.com.au/warranty) for complete details.

WOODWINDS

Wallcoverings » Commercial Wallcoverings

Colour & Finish Options

COLOURWAY CARD



AZ53745 WHITE
WASH



AZ53746 WEATHERED



AZ53747 BARN



AZ53748 BRAZILIAN




AZ53749 BALSA



AZ53750 SHAKER



AZ53751 CONIFER




AZ53752 ELM



AZ53753 POPLAR




AZ53754 MAPLE



AZ53755 OAK



AZ53756 AGED IROKO



AZ53757 CEDAR



AZ53758 TEAK



AZ53759 MAHOGANY



AZ53760 BLACK
WALNUT