

SLIDING LIGHT

Wallcoverings » Commercial Wallcoverings



Brand: **Symphony**

SLIDING LIGHT

Wallcoverings » Commercial Wallcoverings

COLOURWAY CARD

COLOURWAY CARD



AZ53790 WHITEWASH



AZ53791 SOFT
SHADOW



AZ53792 CAST GLASS



AZ53793 SWEDISH
FOG




AZ53794 CHIFFON
BLUSH



AZ53795 TOUCH OF
GOLD



AZ53796 WARM
LAYERS



AZ53797 MELTED

SLIDING LIGHT

Wallcoverings » Commercial Wallcoverings

Inspired by the layered effect of cast glass Sliding Light uses light and shadow to create a dynamic, almost musical, visual experience on your walls.

✓ **Bleach Cleanable**

✓ **Low VOC**

✓ **10% Recycled content**

✓ **Non-Phthalate**

✓ **EPD Certified**

✓ **HPD Certified**

Description

As each ray of light gracefully intertwines, Sliding Light unveils an extraordinary design that transcends conventional boundaries. Inspired by the subtle dance of cast glass, this wallcovering achieves a remarkable transparency effect, orchestrating a nuanced layering of tones.

The interplay of shading creates a visual crescendo, seamlessly blending light and dark variations, creating a mesmerizing symphony is Sliding Light.

Roll Size

137cm wide x 27.4m - Available by the lineal metre

Composition

Vinyl face on a fabric backing Equivalent to 20oz (452 g/m²).

Pattern Repeat Size

61cm V / 137cm H

Environmental Info

Formaldehyde free

Heavy metals free

Perfluorooctanoic acid free

No solvent inks

Low VOC emissions. Any VOCs dissipate quickly (faster than paint) through normal ventilation and have no recognized adverse impact on indoor air quality.

Durability means products do not need to be replaced regularly due to wear and tear and being cleanable, vinyl products are ideal for helping keep commercial environments clean of bacteria.

Baresque will only deal with vinyl manufacturers that comply with applicable state and federal regulations, provide a factory that is safe and clean for its employees to work in, recycle scrap and inks during the manufacturing process to minimize waste related to production.

Fire Rating

Tested in accordance with AS ISO 9705 2003 for the purpose of determining the Group Number classification as required by the Building Code of Australia for the control of fire spread on interior wall and ceiling linings.

The result achieved was:

Classification - Group 2

Specific Extinction - Less than 250m²/kg

SLIDING LIGHT

Wallcoverings » Commercial Wallcoverings

Warranty 5-year warranty. Visit [baresque.com.au/warranty](https://www.baresque.com.au/warranty) for complete details.

Lead Time

- 2-weeks (approx.) from Wednesday, subject to stock availability.
- Additional 1-week for Western Australia.
- Express delivery is available subject to a surcharge. Contact Baresque for details and pricing.

Suggested Installation

Reverse hang / overlap and double cut.

Baresque recommends and supply Roman brand adhesives and primers.

Care Instructions

Use cloth with any of the following in preferred order of use:

- 1: Clear warm water
- 2: Mild solution of liquid detergent and warm water
- 3: Isopropyl Alcohol (a.k.a. rubbing alcohol)

Remove any detergent with a clean, damp cloth. Gently pat dry.

For more difficult stains, dampen a soft white cloth with a solution of household bleach (10% bleach / 90% water). Rub gently.

Rinse with a water dampened cloth to remove bleach concentration.

Do not use solvent based or concentrated abrasive cleaning agents, lacquer thinners or nail polish remover as these may cause discolouration over a period of time.

Always test in an inconspicuous area first.

If care instructions don't deliver the expected results, cease cleaning method immediately and contact Baresque for assistance.

SLIDING LIGHT

Wallcoverings » Commercial Wallcoverings

Colour & Finish Options