**Acoustics** » Acoustic Panels



Brand: **Zintra** 

Collections: Pattern Panel

Applications: Ceilings, Walls

**Acoustics** » Acoustic Panels



Pattern Panel Deepak Detail

**Acoustics** » Acoustic Panels

Discover the 51 classic and contemporary designs available in Zintra Pattern Panels. Effortlessly elevate your space with style, texture, and superior sound absorption with Pattern Panel Deepak

| ✓ Acoustic     | ✓ Bleach Cleanable  | ✓ Easy Clean   |  |
|----------------|---|--|--|
| ✓ Easy Install |   |  |  |
| Description    | Zintra Patterns offers a broad range of classic or contemporary panel designs that can be used on their own, or in conjunction with Zintra backing, to create beautiful, acoustic screens and wall coverings.   |  |  |
|                | With virtually unlimited design options, each pattern can be intricately cut of out Zintra and paired with a matching or contrasting solid Zintra backing panel to achieve a unique aesthetic for walls or ceilings. Experience enhanced noise absorption and easy installation, while enjoying a broad range of neutral and vibrant Colours to suit any space. |  |  |
|                | Deepak, features an asymmetrical pattern  |  |  |
|                | Choose from 51 designs.   |  |  |
|                | Devraj   Elephanta   Fishbone   Foliag<br>Hex   Indus   Jacks   Kali   Kerala   Kr<br>Marquise   Monsoon   Nadu   Noktala   | arata   Bhushan   Circuit   Cirque   Deepak  <br>ge   Gadiva   Garden Art   Ginkgo   Haimati  <br>ishnan   Links   Lost   Malini   Mandava  <br>ar   Origami   Padmesh   Perdita   Pivot   Pixel  <br>an   Sanskrit   Setro   Shard   Siptical   Stone<br>dic   Wamika |  |
|                | Not suitable as a freestanding product.   |  |  |
|                | Elevate your environment with style, a harmonious ambiance with superio   | texture, contrast, and depth, all while creating or sound absorption.  |  |
| Composition    | Zintra Acoustic Panel - 100% Solutio  | n Dyed (Colour Through) Polyester  |  |
|                | 12mm (1/2") - Density 2.4 kg /m² 0.5 lb/ft²   |  |  |
|                | 24mm (1" ) - Density 3.6 kg /m² 0.75 lb/ft²   |  |  |
| Sustainability | Zintra is made from 100% recyclable materials.  |  |  |
|                | • 60% post-consumer recycled content from PET bottles.  |  |  |
|                | • 35% pre-consumer recycled content from PET chips  |  |  |
|                | • 5% polylactic acid (PLA)  |  |  |



**Acoustics** » Acoustic Panels

| Dimensions                | Pattern Only   |  |
|---------------------------|--|--|
|                           | 1220mm (48") x 2745mm (108') x 12mm (1/2")   |  |
|                           | Pattern on Backer  |  |
|                           | 1220mm (48") x 2745mm (108') x 24mm (1")   |  |
|                           |  |  |
| Fire Rating               | ASTM-E84 – Class A classification<br>AS ISO 9705 – 2003 – Group 1 classification<br>EN-13501 – B-s2-d0 classification  |  |
| Supplied As               | Ships Flat Pack  |  |
|                           | Go to the Technical Documents and download the Installation Guide for more details.  |  |
| Suggested<br>Installation | Go to Technical Documents and download the Installation Guide for more details.  |  |
| Care Instructions         | Vacuum to remove dust.   |  |
|                           | Dab Zintra with a damp clean cloth and mild solution of liquid detergent and warm water. Repeat using only clean water, then pat dry with a lint free cloth.       |  |
|                           | For difficult stains, use a solution of household bleach (10% bleach / 90% water). To remove the bleach, repeat using a clean, water dampened cloth, then pat dry. |  |
|                           | Always test in an inconspicuous area first and if you don't see the expected results, contact us.  |  |
| Warranty                  | Visit FAQ for more details.  |  |
| Customisable              | The Zintra Acoustic Solutions range is customisable to your project. Please get in touch with your local contact for details.                                      |  |



Acoustics » Acoustic Panels

#### Additional Comments Patterns Only NRC Rating

- Directly Mounted: 0.45
- With 2" (50mm) Air Gap: 0.85
- With 6" (152mm) Air Gap: 0.90
- With 12" (305mm) Air Gap: 0.95

#### **Patterns on Backer NRC Rating**

- Directly Mounted: 0.75
- With 2" (50mm) Air Gap: 0.95
- With 6" (152mm) Air Gap: 1.0
- With 12" (305mm) Air Gap: 1.0

### How to Specify

- 1. Select Pattern design
- 2. Select Pattern only or Pattern on Backer.
- 3. Select Zintra Colour.

If selecting backer please state which colour is the pattern layer and which is the backer.

### Colour & Finish Options

#### Zintra 12mm Solid PET







**Acoustics** » Acoustic Panels



Slate









Twilight