

POLKA TEN

Acoustic Solutions - Zintra Pressed Tiles - Ceilings - Zintra Pressed Tiles.



Texture:
 Lustre:
 Transparency:

DESCRIPTION / FEATURES	<p>With a range of standard pressed designs you can give your suspended ceiling texture and definition, whilst retaining the acoustic benefits of a tile inlay system. Baresque Zintra Acoustic Pressed Tile is the perfect solution for your application where acoustic performance as well as aesthetics are required.</p> <p>Zintra wide range of colours and ease of use make it the ideal material for commercial, hospitality and institutional projects.</p>
BRAND SPEC	<p>Fire:</p> <p>In accordance with AS/NZS 3837, Zintra Acoustic Panel achieved a result of</p> <p>Classification - Group 1</p> <p>Specific Extinction - Less than 250m²/kg</p>
HOW TO SPECIFY	<ol style="list-style-type: none"> 1. Size 2. Zintra Colour 3. Pressed Pattern
COMPOSITION	<p>Zintra Acoustic Panel - 100% Solution Dyed (Colour Through)</p> <p>Polyester</p>
FIRE RATING	<p>Zintra Acoustic Panel was tested in accordance with AS ISO 9705</p>



	<p>2003 for the purpose of determining the Group Number classification as required by the Building Code of Australia for the control of fire spread on interior wall and ceiling linings.</p> <p>The result achieved was: Classification - Group 1 Specific Extinction - Less than 250m²/kg</p>
STANDARD SIZE	595mm x 595mm or 595mm x 1190mm
FINISHES AVAILABLE	Zintra Acoustic. Available in the Zintra Acoustic 24mm colour range.
INDOOR/OUTDOOR	Indoor only
WET AREAS	No
CUSTOMISABLE	Size - Yes. Tool making fees apply Zintra Colour - Yes. 200 sheet minimum
LEAD TIME	2-3 weeks + 1 week for Western Australia
SUGGESTED INSTALLATION	<p>Baresque's Zintra Acoustic Pressed Tiles are designed to fit into new or existing suspended ceiling grid systems or direct stuck onto the wall.</p> <p>If used as wall cladding, the tolerance of +/- 2mm on the pressed section should be taken into account. It is recommended to leave an express gap between panels to avoid noticing any variation in thickness.</p> <p>Check out the Baresque Zintra Panel Handling Fabrication Installation Guide on the DOWNLOADS tab for more details.</p>
CARE INSTRUCTIONS	<p>Remove spills immediately using damp, clean cloth.</p> <p>Dab Zintra with a clean, soft white cloth dampened with a mild solution of liquid detergent and warm water. Repeat using only clean</p>



	<p>water, then pat dry with a lint free cloth.</p> <p>Avoid using wax polishes, solvents or concentrated abrasives.</p> <p>For more difficult stains, dampen a soft white cloth with a solution of household bleach (10% bleach / 90% water). Dab gently. Repeat using only a clean, water dampened cloth to remove bleach concentration then pat dry with a lint free cloth.</p> <p>Always test in an inconspicuous area first. If care instructions don't deliver the expected results, cease cleaning method immediately and contact Baresque for assistance.</p>
ENVIRONMENTAL INFORMATION	

Easily recycled through standard recycling channels