

## TESSELATE

Zintra Etch - zintra etch



Texture:

Lustre:

Transparency:

DESCRIPTION / FEATURES	
	<p>Acoustic absorption meets dynamic 3D design with Baresque™s new Zintra Etch. Featuring a range of subtle textures, Zintra Etch will help deliver a cutting-edge but welcoming atmosphere to your next commercial, hospitality or institutional interior.</p> <p>Zintra Etch is available in an extensive range of understated to statement colours and will cultivate calming environs with this cost-effective sound and design solution. Zintra Etch is also easily able to tied back to plain Zintra sheets or talk to us about replicating your Etch pattern in Zintra on Zintra.</p> <p>Zintra Etch Features:</p> <ul style="list-style-type: none"> <li>• Suitable for wall cladding or ceilings</li> <li>• NRC equals at least 0.45</li> <li>* pattern matching with seamless hidden joins (excl VJ Angle and Kaleido)</li> <li>* 2795mm sheet size allows join-free floor-to-ceiling and easy fitout</li> <li>• Designs easily customised to suit your needs</li> </ul>

<b>HOW TO SPECIFY</b>	<ol style="list-style-type: none"> <li>1. Design</li> <li>2. Colour</li> <li>3. Zintra Thickness (12mm or 24mm)</li> </ol>
<b>COMPOSITION</b>	Zintra Acoustic Panel - 100% Polyester
<b>FINISHES AVAILABLE</b>	Matt. Check out the Zintra Acoustic Panel colour range in the Downloads section
<b>SHEET SIZE</b>	2795mm H x 1195mm H
<b>THICKNESS</b>	12mm or 24mm
<b>WEIGHT</b>	12mm = 2.4kg/m <sup>2</sup> , 24mm = 3.5kg/m <sup>2</sup>
<b>INDOOR/OUTDOOR</b>	Indoor only
<b>WET AREAS</b>	No
<b>SUGGESTED INSTALLATION</b>	Adhere to substrate using contact adhesive or Liquid Nails. Panel can be mechanically fixed using details similar to glass fittings.
<b>LEAD TIME</b>	2-3 weeks
<b>CUSTOMISABLE</b>	Design - Yes Colour - Minimums apply. Contact Baresque for details
<b>THERMOFORMABLE</b>	No
<b>FIRE</b>	Fire: In accordance with AS/NZS 3837, Zintra Acoustic Panel achieved a result of Classification - Group 1 Specific Extinction - Less than 250m <sup>2</sup> /kg
<b>ADDITIONAL COMMENTS</b>	Etch is a 3mm deep V groove. Not suitable as a free standing product.
<b>SUPPLIED AS</b>	Full sheets for cutting to size on site as required
<b>FABRICATION</b>	Cut with Stanley knife and straight edge on site
<b>REFINISHABLE</b>	No



**baresque.com.au**  
e info@baresque.com.au  
p 1300 306 399

<b>CARE INSTRUCTIONS</b>	Remove spills immediately using damp, clean cloth. Carpet and fabric cleaners can be used.  Always test in an inconspicuous area first. If care instructions don't deliver the expected results, cease cleaning method immediately and contact Baresque for assistance.
<b>ENVIRONMENTAL INFORMATION</b>	Easily recycled through standard recycling channels