

SMOOTH PLASTER

New Releases - Wallcoverings - Reatec



Texture: 1
 Lustre: 1
 Transparency: 1

<p>DESCRIPTION / FEATURES</p>	<p>Reatec is a durable and realistic architectural film with a pressure sensitive adhesive and air removal system backing.</p> <p>Utilising state of the art, multi layer printing and minute embossing, its appearance is almost indistinguishable from real wood or stone.</p> <p>Reatec is stain and solvent/chemical resistant, anti-bacterial, anti-mould, colorfast, washable, scrubbable, and abrasion resistant. A pdf with full Reatec Test Results can be found on the product Downloads tab on the website.</p> <p>Reatec can be stretched to cover the corners and curves and is suitable for both indoor and outdoor uses including kitchens and bathrooms.</p> <p>Go to the DOWNLOADS tab for our Reatec Additional Spec Sheet and Installation Guide.</p>
<p>BRAND SPEC</p>	<p>Reatec</p>
<p>COMPOSITION</p>	<p>Reatec is a durable and realistic architectural film with a pressure sensitive adhesive and air removal system backing 350 g/m²</p>

PATTERN REPEAT	N/A
WEIGHT	350g/m ²
FIRE RATING	<p>In accordance with AS/NZS 3837 and AS 5637.1:2015</p> <p>Classification - Group 1</p> <p>Specific Extinction - Less than 250m²/kg</p> <p>This product was deemed suitable for testing in accordance with AS 5637.1:2015 and testing was performed in accordance with AS/NZS 3837 for the purposes of Group Number Classification as specified in the NCC Volume One Specification C1.10 Clause 4.</p>
WIDTH	122cm
ROLL LENGTH	50m - Available by the lineal metre
LEAD TIME	2 weeks (approx) from Wednesday subject to stock availability. + 1 week for Western Australia. Express delivery is available subject to a surcharge. Contact Baresque for details and pricing.
SUGGESTED INSTALLATION	<p>Reatec is a specialised product and should only be installed by a trained installer. It is strongly recommended that the installation instructions found on the product "Downloads" tab are read and completely understood. Feel free to contact Baresque with any installation questions. _x000D_</p> <p>_x000D_</p> <p>As Reatec is a thin film, the substrate should be prepared as smooth as possible so as to avoid visible unevenness. Reatec is able to be installed and repaired on-site, resulting in virtually zero downtime for both interior and exterior applications.</p> <p>Baresque recommend and supply Roman brand adhesives and primers.</p>
CARE INSTRUCTIONS	Wipe material with a clean, soft cloth dampened with a mild solution of liquid detergent and warm water. Repeat using only clean water,



then dry with a lint free cloth.

Avoid using wax polishes, solvents or concentrated abrasives.

For more difficult stains, dampen a soft white cloth with a solution of household bleach (10% bleach / 90% water). Rub gently. Rinse with a water dampened cloth to remove bleach concentration.

Always test in an inconspicuous area first. If care instructions don't deliver the expected results, cease cleaning method immediately and contact Baresque for assistance.