

**BHUSHAN**  
 2D Perforated



Texture: 1  
 Lustre: 1  
 Transparency: 1

<b>DESCRIPTION / FEATURES</b>	Designs perforated through finishes sandwiched around a Ply or Resin (Black or White) core. Core selection not required for Zintra Acoustic or Elements Metal.
<b>HOW TO SPECIFY</b>	<ol style="list-style-type: none"> <li>1. Design name</li> <li>2. Colour front / colour back</li> <li>3. Core type</li> <li>4. Sheet Size</li> <li>5. Thickness</li> </ol>
<b>FINISHES AVAILABLE</b>	Go to the <b>DOWNLOADS</b> tab and click on the 2D Perforated Screens Finish Guide for details
<b>SHEET SIZE</b>	Go to the <b>DOWNLOADS</b> tab and click on the Screen Size pdf for standard sizes.
<b>THICKNESS</b>	Depends on your finish selection. Go to the <b>DOWNLOADS</b> tab and click on the 2D Perforated Screens Finish Guide for details
<b>INDOOR/OUTDOOR</b>	Indoor only except for Elements Metal Outdoor and Lightblocks Ice
<b>WET AREAS</b>	Elements Metal or Lightblocks Ice screens can be used in wet areas.

<b>SUGGESTED INSTALLATION</b>	<p>* An expansion gap of 1mm per 1 meter of product should be allowed for when setting out your 2D Perforated Screens.</p> <p>* Mechanical fixing is strongly recommended for all ceiling installations</p> <p>* Most glass fittings can be used.</p> <p>See Baresque 2D Perforated Screen Systems Guide or Screens Handling, Fabrication and Installation Guide for more details.</p>
<b>LEAD TIME</b>	<p>3 weeks (approx, Reatec - 4 weeks) + 1 week for Western Australia. Express delivery may be available subject to a surcharge. Contact Baresque for details and pricing.</p>
<b>CUSTOMISABLE</b>	<p>Size - Yes. Subject to additional charges.</p> <p>Design - 10 sheet minimum</p> <p>Colour - Lightblocks Board Colours and Elements Metal Screens can be customised for a 10 sheet minimum. Baresque's standard colour range for Elements Metal is Dulux. Interpon colours are subject to a surcharge.</p>
<b>THERMOFORMABLE</b>	<p>No</p>
<b>ADDITIONAL COMMENTS</b>	<p>Plywood is a natural product, thus has natural imperfections and knots. Perforations cut into screens may expose knots and will be visible on finished product. The edges of the core cannot be sealed. Also available in single sided.</p> <p>Designs are progressive and the biscuit between panels allows for a virtually seamless join. The cores provide strength while the perforations mean the panels are light weight and able to be handled easily.</p>



**baresque.com.au**  
e info@baresque.com.au  
p 1300 306 399

<b>FABRICATION</b>	Standard wood-working tools except Elements Metal which requires metal fabricating tools. See Baresque Screens Handling, Fabrication and Installation guide for more details.
<b>REFINISHABLE</b>	Depends on your finish selection. Go to the DOWNLOADS tab and click on the 2D Perforated Screens Finish Guide for details.
<b>CARE INSTRUCTIONS</b>	Screens

## CARE INSTRUCTIONS

For all Screens, remove spills immediately Always use a clean, white, soft cloth and test any cleaning in an inconspicuous area first.

For Zintra Acoustic Screens - carpet and fabric cleaners can be used. Always test in an inconspicuous are first.

For all other Screens - Use cloth with any of the following in preferred order of use

\* Clear warm water

\* Mild solution of liquid detergent and warm water

\* Isopropyl Alcohol (a.k.a. rubbing alcohol)

Remove any detergent with a clean, damp cloth. Gently pat dry.

A 1:10 bleach to water solution can be used to clean Lightblocks Board, Reatec and Elements Metal Screens.

Always test in an inconspicuous area first. If care instructions don't deliver the expected results, cease cleaning method immediately and contact Baresque for assistance.