

## SILK STRANDS

### Lucere Encapsulated



Texture: 1

Lustre: 2

Transparency: 2

<b>DESCRIPTION / FEATURES</b>	<p>Lucere is a poured acrylic resin which is then used to encapsulate various materials providing a sheet with unparalleled depth and clarity</p> <ul style="list-style-type: none"> <li>* Perfect for partitions, screens and lighting</li> <li>* Fabricated with standard wood working tools</li> <li>* Unparalleled depth and clarity</li> <li>* Fully refinisable to matt or gloss</li> </ul>
<b>HOW TO SPECIFY</b>	<ol style="list-style-type: none"> <li>1. Design / Colour name</li> <li>2. Sheet size</li> <li>3. Sheet thickness</li> <li>4. Surface finish for each side</li> <li>5. Pattern direction - horizontal or vertical. See Directions Guide for details</li> </ol>
<b>COMPOSITION</b>	<p>Ribbons embedded in acrylic. Silk Strands is able to be laid horizontally OR vertically. Unless otherwise specified, material will be laid running vertically. See Directions Guide for details</p>
<b>SURFACE FINISH</b>	<p>Gloss, Matt or Gloss/Matt</p>
<b>SHEET SIZE</b>	<p>3050mm x 1220mm, 2440mm x 1220mm or 2000mm x 1000mm</p>

<b>THICKNESS</b>	6mm, 8mm or 11mm. 3050mm x 1220mm sheet size available in 8mm or 11mm only. A thickness tolerance of +/- 10% may occur in any resin
<b>WEIGHT</b>	6mm - 6kg/m <sup>2</sup> , 8mm - 8kg/m <sup>2</sup> , 11mm - 11kg/m <sup>2</sup>
<b>INDOOR/OUTDOOR</b>	Indoor use only
<b>WET AREAS</b>	Yes. Edges must be sealed
<b>PATTERN REPEAT</b>	N/A
<b>SUGGESTED INSTALLATION</b>	An expansion gap of 1mm per 1 meter of product should be allowed for when setting out your sheets. Most glass fittings can be used. See Baresque Lucere Handling, Fabrication and Installation guide for more details.
<b>LEAD TIME</b>	8 weeks (approx) from Wednesday + 1 week for Western Australia. Express delivery is available subject to a surcharge. Contact Baresque for details and pricing.
<b>CUSTOMISABLE</b>	Yes. 10 sheet minimum
<b>THERMOFORMABLE</b>	Yes but subject to sheet specific ordering and manufacture. Contact Baresque for details.

<b>ADDITIONAL COMMENTS</b>	<ol style="list-style-type: none"><li>1. Being handmade, slight imperfections in Lucere are deemed acceptable. These slight imperfections may include small bubbles in the interlayer or slight surface texture imperfections. Any imperfection that is not visible one (1) meter away from the panel is deemed within commercial tolerance.</li><li>2. Lucere sheets may not be perfectly flat. Due to this, it is always suggested that the sheet be fully framed or mechanically fixed.</li><li>3. Natural products used in Lucere are seasonal. As such, variations in colour and density may occur between samples and the order. If this detail is critical, a sample of current stock should be produced for final approval which will add up to 3 weeks to the ordering process.</li><li>4. The interlayers can also be run horizontally. Contact Baresque for details.</li><li>5. Lucere can be used as a splashback but NOT behind a stove or cooktop. We recommend a minimum distance of 300mm from stove or cooktop.</li></ol>
----------------------------	--



**baresque.com.au**  
e info@baresque.com.au  
p 1300 306 399

<b>FABRICATION</b>	Standard wood working tools. See Baresque Lucere Handling, Fabrication and Installation guide for more details.
<b>REFINISHABLE</b>	Fully refinishable to matt or gloss

**CARE INSTRUCTIONS**

\* Do not use glass cleaning products, acetone, gasoline, benzene, lacquer thinner, chlorinated solvents, gritty abrasive scouring compounds, or alkaline cleaners to clean Lucere as damage to the sheet will occur

\* Use warm water, mild detergent, and a soft sponge, cloth, or chamois to clean Lucere

\* Surface contamination may be cleaned using kerosene, hexane, or aliphatic naphtha, or any acrylic cleaner, such as Novus. Always follow manufacturers recommended use and safety procedures

\* Remove any oily residue left behind from solvent cleaning with detergent and water

Do not use squeegee, scraper, or synthetic rags that may scratch Lucere

When cleaning, never scrub. Gently wipe surface with a soft scratch free cloth.

Always test in an inconspicuous area first. If care instructions don't deliver the expected results, cease cleaning method immediately and contact Baresque for assistance.

REFINISHING - Contact Baresque for details



**baresque.com.au**  
e info@baresque.com.au  
p 1300 306 399

<b>ENVIRONMENTAL INFORMATION</b>	Lucere panels are easily recycled. Contact your nearest Baresque branch for details.
----------------------------------	--